

Sec. 9

JACK NUT® INSTALLATION TOOLS

Tool comes with 16856 (6-32 Thread) Installation Rod



Part No. 14157 Professional Jacknut® Installation Tool

UNIT PACKAGE: 1

An economical tool for rapidly installing Jack Nuts in any material. Takes interchangeable screw rods. Just screw rod into Jack Nut, push into hole, squeeze to set and remove. Sets all size Jack Nut Threaded Inserts.

Jacknut® Installation Rods

Use w/14157 Installation Tool



Auveco Part No.	Unit Pkg.	Thread
16856	1	6-32
14158	1	10-24
14159	1	1/4-20
14160	1	4mm
14161	1	5mm
14162	1	6mm

Part No. 14156 Friction Wrench



For use when installing a limited quantity of Jack Nuts. Insert the wrench between the screw and the head of the fastener, hold wrench and run in screw to set Jack Nut.

UNIT PACKAGE: 10




Mirror Mounting Screws And Jack Nuts

For additional information refer to listings on pages 21 and 52.

Auveco Part No.	Description	Unit Pkg.
13231	1/4-20 x 7/8" Screw (Phos.)	25
13232	1/4-20 x 7/8" Screw (Phos) & Jack Nut®	25
14947	M6 x 26mm Screw (Chrome)	25
14976	1/4-20 x 1-1/4" Screw (Stainless Steel)	25
14977	1/4-20 x 1-1/4" Screw (Stainless Steel) & Jack Nut®	10

RUBBER NUT INSERTS

Neoprene Rubber With A Brass Nut



Part Number	Unit Pkg.	Thread	(A) Head Dia.	(B) Overall Length	(C) Shank Length	(D) Shank Dia.	(E) Head Height	Hole Size	Grip Range
19911	25	#6-32	.433	.496	.441	.311	.055	5/16	.015-.156
19917	15	5/16-18	.870	.721	.595	.626	.126	5/8	.015-.156
19918	15	M5-.8	.551	1.570	1.519	.375	.051	3/8	.808-1.182