

# Sec. 12

## Wire Loom & Primary Wire

(Split Flexible Tubing)

Can withstand Maximum Temperature of 345°F



I.D. 1/4" - O.D. 3/8"  
Nylon 6 - Black

**14197** 10' Length  
**14201** 50' Length (Bulk)



I.D. 3/8" - O.D. 9/16"  
Nylon 6 - Black

**14198** 10' Length  
**14202** 50' Length (Bulk)



I.D. 1/2" - O.D. 11/16"  
Nylon 6 - Black

**14199** 10' Length  
**14203** 50' Length (Bulk)



I.D. 5/8" - O.D. 13/16"  
Nylon 6 - Black

**20536** 50' Length



I.D. 3/4" - O.D. 15/16"  
Nylon 6 - Black

**14200** 10' Length  
**14204** 50' Length (Bulk)



I.D. 1" - O.D. 1-1/8"  
Nylon 6 - Black

**18194** 25' Length

## PRIMARY WIRE

### General Purpose

Standard PVC Insulation (SE/GPT Type)  
Suitable for Most Automotive Applications  
Free Stripping, Abrasion Resistant  
Meets Most O.E.M. Vehicle Standards

UNIT PACKAGE: 1 Roll

The lower the gauge number, the thicker the wire  
(i.e. 10 gauge is thicker than 16 gauge)



Gauge	Stranding	O.D.	Auveco Part No				
			Red	White	Black	Blue	Length
18	16 x 30	.092	<b>20486</b>	<b>20487</b>	<b>20488</b>	<b>20489</b>	45 Ft.
16	19 x 29	.104	<b>20490</b>	<b>20491</b>	<b>20492</b>	<b>20493</b>	35 Ft.
12	19 x 25	.142	<b>20494</b>	<b>20495</b>	<b>20496</b>	<b>20497</b>	15 Ft.
10	19 x 23	.175	<b>20498</b>	<b>20499</b>	<b>20500</b>	<b>20501</b>	10 Ft.

### 25 Foot Spool

Gauge	Stranding	O.D.	Auveco Part No					
			Red	White	Black	Blue	Green	Yellow
14	19 x 27	.117	<b>12419</b>	<b>12420</b>	<b>12421</b>	<b>12422</b>	<b>15239</b>	<b>15240</b>

### 100 Foot Spool

Gauge	Stranding	O.D.	Auveco Part No						
			Red	White	Black	Blue	Green	Yellow	Brown
20	10 x 30	.085	<b>21339</b>	<b>21340</b>	<b>21341</b>	<b>21342</b>	<b>21343</b>	<b>21344</b>	<b>21345</b>
18	16 x 30	.092	<b>12423</b>	<b>12424</b>	<b>12425</b>	<b>12426</b>	<b>12427</b>	<b>12428</b>	<b>15256</b>
16	19 x 29	.104	<b>12429</b>	<b>12430</b>	<b>12431</b>	<b>12432</b>	<b>12433</b>	<b>12434</b>	<b>15257</b>
14	19 x 27	.117	<b>12435</b>	<b>12436</b>	<b>12437</b>	. . . .	<b>12439</b>	<b>12440</b>	<b>15258</b>
12	19 x 25	.142	<b>12441</b>	<b>12442</b>	<b>12443</b>	<b>12444</b>	<b>15259</b>	<b>15260</b>	. . . .
10	19 x 23	.175	<b>12445</b>	. . . .	<b>12447</b>	<b>12448</b>	. . . .	<b>15263</b>	. . . .