

Sec. 8

Finished USS (Coarse) & SAE (Fine) Hexagon Nuts

Zinc & Yellow Plated
High Alloy
Grade 8



Auveco Part No.	Thread Size	Hex Width	Unit Pkg.
9300	1/4"-20 USS	7/16"	100
9307	1/4"-28 SAE	7/16"	100
9301	5/16"-18 USS	1/2"	100
9308	5/16"-24 SAE	1/2"	100
9302	3/8"-16 USS	9/16"	100
9309	3/8"-24 SAE	9/16"	100
9303	7/16"-14 USS	11/16"	50
9310	7/16"-20 SAE	11/16"	50
9304	1/2"-13 USS	3/4"	50
9311	1/2"-20 SAE	3/4"	50
9305	5/8"-11 USS	15/16"	25
9312	5/8"-18 SAE	15/16"	25
9306	3/4"-10 USS	1-1/8"	25

NUTS

Grade 8
Finished USS (Coarse) & SAE (Fine) Hex Nuts



Fully Certified
Proof Load: 150,000 PSI
C24-C32 Max. Rockwell Hardness For 1/4 thru 5/8
C26-C34 Max. Rockwell Hardness For 3/4 thru 1
Zinc & Yellow Plated

Auveco Part No.	Thread Size	Hex Width	Unit Pkg.
15640	1/4"-20 USS	7/16"	100
15649	1/4"-28 SAE	7/16"	100
15641	5/16"-18 USS	1/2"	100
15650	5/16"-24 SAE	1/2"	100
15642	3/8"-16 USS	9/16"	100
15651	3/8"-24 SAE	9/16"	100
15643	7/16"-14 USS	11/16"	50
15652	7/16"-20 SAE	11/16"	50
15644	1/2"-13 USS	3/4"	50
15653	1/2"-20 SAE	3/4"	50
16983	9/16"-12 USS	7/8"	25
15645	5/8"-11 USS	15/16"	25
15654	5/8"-18 SAE	15/16"	25
15646	3/4"-10 USS	1-1/8"	15

Refer to Assortments 1020, 1021, 1030 & 1031 in the green pages.



**Display Boards
Are Great Selling Tools.
Use Them To Help Boost
Your Sales.
Refer To The Color Pages
At The Front Of The
Catalog.**

**Do You Want Your Customers To
Know You Use The Best Body
Hardware & Specialty Fasteners
Available?**

**Promotional Products And Apparel
Bearing The  Logo Promote
Your Identity As A Professional.**